



EcoTouch® PINK® FIBERGLAS™ Insulation with PureFiber® Technology

Submittal Sheet

Contractor _____ Project _____

Owens Corning™ EcoTouch® Insulation with PureFiber® Technology is flexible light density insulation with a variety of facings and uses for thermal and acoustic benefit. EcoTouch® Insulation is dimensionally stable and will not slump within the cavity. Due to its inorganic fibers, EcoTouch® Insulation is not a food source for mold, it will not rot or mildew and it is not corrosive to steel, copper or aluminum.

ASTM C665 Classification	Description
Type I	Blankets without membrane coverings.
Type II	Blankets with nonreflective membrane coverings:
Class A	Membrane-faced surface flame spread of 25 or less.
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm ² (0.11 Btu/ft ² ·xs) or greater.
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder.
Category 2	Membrane is not a vapor retarder.
Type III	Blankets with reflective membrane coverings:
Class A	Membrane-faced surface flame spread of 25 or less.
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm ² (0.11 Btu/ft ² ·xs) or greater.
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder.
Category 2	Membrane is not a vapor retarder.

Unfaced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **wood or metal** framing to allow for friction fit installation. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type I, Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- UL File #BKNV 3576 (Fire rated assemblies)

- | | |
|-----------------------------------|-------------------------------------|
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-25 8" |
| <input type="checkbox"/> R-15 3½" | <input type="checkbox"/> R-30C 8¼" |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-20 5½" | <input type="checkbox"/> R-38C 10¼" |
| <input type="checkbox"/> R-21 5½" | <input type="checkbox"/> R-38 12" |
| <input type="checkbox"/> R-22 6¾" | |

Kraft Faced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **wood or metal** framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type II, Class C
- ASTM E84 Not rated
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- ASTM E96 Perm Rating -1 perm
- UL File #BKNV 3576 (Fire rated assemblies)

- | | |
|-----------------------------------|-------------------------------------|
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-22 6¾" |
| <input type="checkbox"/> R-15 3½" | <input type="checkbox"/> R-30C 8¼" |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-20 5½" | <input type="checkbox"/> R-38C 10¼" |
| <input type="checkbox"/> R-21 5½" | <input type="checkbox"/> R-38 12" |

Unfaced—Sound Attenuation Batts

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **metal** framing to allow for friction fit installation. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type I, Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (2½", 3½")
- UL File #BKNV 3576 (Fire rated assemblies)

- | | |
|----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-8 2½" | <input type="checkbox"/> R-11 3½" |
|----------------------------------|-----------------------------------|

FSK or PSK Faced—EcoTouch® Flame Spread 25 Batt Insulation

Fiberglass insulation with facing that can be left exposed that is designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **wood or metal** framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type II (PSK) or Type III (FSK), Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E96 Perm Rating -.02 perm

- | | |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-21 5½" |
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-38 12" |

Visit www.ocbuildingspec.com to access a variety of learning, application and design resources to build your spec. For current product availability, please contact an Owens Corning Distributor or Area Sales Manager. Visit division7.owenscorning.com or download the App on the iTunes Store (iPhone/iPad) or Google Play store (Android)



EcoTouch® PINK® FIBERGLAS™ Insulation with PureFiber® Technology

Submittal Sheet

Foil Faced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **metal** framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type III, Class B and C
- ASTM E84 75/150
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- ASTM E96 Perm Rating -I perm
- UL File #BKNV 3576 (Fire rated assemblies)

- R-11 3½" R-19 6¼"
- R-13 3½" R-30 9½"

Kraft Faced—Sonobatts® Insulation

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of suspended ceiling assemblies. 24" x 48" to fit on top of most drop in ceiling tile. Meets ASTM Standard C665.

- ASTM C665 Type II, Class C
- ASTM E84 Not Rated
- ASTM C1338 Mold/mildew resistant
- ASTM E96 perm Rating -I perm
- ASTM C518
- ASTM E90, E413
- UL File #BKNV 3576 (Fire rated assemblies)

- R-11 3½" R-19 6¼"
- R-13 3½"

Kraft Faced—PROPINK® FastBatt

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in **wood** framing to allow for friction fit installation. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type II, Class C
- ASTM E84 not rated
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- ASTM E96 Perm Rating -I perm
- UL File #BKNV 3576 (Fire rated assemblies)

- R-13 3½" R-19 6¼"
- R-15 3½" R-21 5½"

Unfaced—EcoTouch® QuietZone® Acoustic Batt Insulation

Fiberglass insulation designed to improve acoustic performance of wall assemblies. Fits tightly in **wood** framing to allow for friction fit installation. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type I, Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM E90, E413 (3½", 5½")
- UL File #BKNV 3576 (Fire rated assemblies)

- 3½" 5½"

Unfaced—Sonobatts® Insulation

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of suspended ceiling assemblies. 24" x 48" to fit on top of most drop in ceiling tile. Meets ASTM Standard C665.

- ASTM C665 Type I, Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- UL File #BKNV 3576 (Fire rated assemblies)

- R-11 3½" R-19 6¼"

Kraft Faced—EcoTouch® QuietZone® Acoustic Batt Insulation

Fiberglass insulation designed to improve acoustic performance of wall assemblies. Fits tightly in **wood** framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications. Meets ASTM Standard C665.

- ASTM C665 Type II, Class C
- ASTM E84 Not Rated
- ASTM C1338 Mold/mildew resistant
- ASTM E90, E413 (3½")
- ASTM E96 Perm Rating -I perm
- UL File #BKNV 3576 (Fire rated assemblies)

- 3½"



Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Nothing contained in this bulletin shall be considered a recommendation.

Scientific Certification Systems (SCS) provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.scs-certified.com.

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

Pub. No. 10019001. Printed in U.S.A. May 2014. The color PINK is a registered trademark of Owens Corning. © 2014 Owens Corning Insulating Systems, LLC. All Rights Reserved.

GREENGUARD Gold applies to EcoTouch® Unfaced and Faced Batts, Unbonded Loosefill Insulation, Flame Spread 25 FSK and PSK Faced Insulation, Sound Attenuation Batt Insulation, Sonobatts® Unfaced and Kraft-Faced Insulation, Metal Building Insulation. GREENGUARD Formaldehyde Free applies to EcoTouch® Unfaced Batts and Unbonded Loosefill Insulation.

SCS 58% recycled content applies to EcoTouch® Faced Batts and Rolls, Loosefill Insulation, Metal Building Insulation products, and Flexible Air Handling products. SCS 65% recycled content applies to EcoTouch® Unfaced Insulation.

Environmental product declaration applies to EcoTouch® Unfaced, Faced, FSK/PSK, and Foil-Faced Insulation.