

NEW!



Trumbull®

**TRULO® LO ODOR
Low-Odor Asphalt**

OPTIMUM PERFORMANCE—WITHOUT THE ODOR.

Introducing TruLo® Lo Odor asphalt. It takes most of the annoying odor out of every hot asphalt job.

THE SWEET SMELL OF INNOVATION.

Owens Corning uses a patent-pending technology specifically formulated to neutralize asphalt odor without impacting asphalt performance.

Testing shows:

- A 50% odor reduction in *TruLo* Lo Odor asphalt as compared to Trumbull standard asphalt
- When compared to leading competitive low-odor asphalts and additives, *TruLo* Lo Odor asphalt was 45% more effective at reducing odor-causing compounds

NOW ODOR DOESN'T HAVE TO DICTATE SCHEDULING.

Many customers are understandably bothered by the odor of typical built-up roofing. *TruLo* Lo Odor asphalt:

- Helps you avoid costly night and weekend work scheduling due to odor issues
- Was developed to allow BURA to be used for even the most odor-sensitive sites, such as schools, restaurants and hospitals
- Significantly reduces odor complaints

KEEP YOUR KETTLE ROUTINE.

TruLo Lo Odor asphalt follows the same kettle processing as standard asphalt—there is no messy, dangerous mixing of additives.

- Works effectively to control odor both on the roof and at the kettle
- Available at Trumbull distributor locations nationwide
- Call 1-800-GET-PINK™ for the distributor nearest you



**LOW
ODOR**

**TYPICAL PHYSICAL CHARACTERISTICS
FOR TRULO® LO ODOR***

	TYPE I** Min. Max.		TYPE II** Min. Max.		TYPE III Min. Max.		TYPE IV Min. Max.	
Softening Point (°F)	140	150	165	175	195	205	215	225
Penetration Units:								
@ 77°F	20	35	20	30	17	24	15	22
Flash Point (°F)								
minimum	525		525		525		525	
typical [†]	550		550		550		550	
Ductility @ 77°F (cm)	13		4.0		3.0		2.0	
Solubility in Trichloroethylene %	99.8		99.8		99.8		99.8	
Typical Application Temperature for Hand Mopping EVT @ 125 CPS ± 25°F ^{††}	350		375		430		450	
For Machine Spreader EVT @ 75 CPS ± 25°F ^{††}	370		395		455		475	

* Meets or exceeds all ASTM D 312 requirements.

** Available by special order only.

[†] Check the Owens Corning Web site for regional differences in typical flash points.

^{††} Trumbull asphalt typically has EVTs in the following range for this product. For specific EVTs for a product from a particular Trumbull Plant, check our Web site at www.trumbullasphalt.com or call 1-800-GET-PINK™.



**OWENS CORNING
ROOFING AND ASPHALT, LLC**
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK™
www.owenscorning.com

Pub. No. 10009927. Printed in U.S.A. September 2008. THE PINK PANTHER™ & © 1964–2008 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2008 Owens Corning.

